

| Parameter | | Value |
|--------------------------|---|----------------------------|
| Physical Parameter | LED Type | IMD 4in1 |
| | Pixel Pitch (mm) | 1.5883 |
| | Panel Dimensions (W x H x D) / (mm) | 610 x 343 x 80 |
| | Pixel Per Panel | 384 x 216 |
| | Panel Weight (kg) | 9.2 |
| | Panel Material | Die Casting Aluminium |
| | Module Dimensions (W x H) / (mm) | 152.5 x 343 |
| Optoelectronic Parameter | Brightness (nit) | 1000 |
| | Refresh Rate (Hz) | 7680 |
| | Gray Scale (Bit) | 15 |
| | Contrast Ratio | 5500:1 |
| | Colour Temperature (K) | 6500 |
| | Viewing Angle (H/V) (°) | 160 / 140 |
| | Driving Type | 1 / 18 |
| | AC Operating Voltage (V) | 100 - 240 |
| | Power Consumption (Max / Average) (W/M ²) | 810 / 270 |
| | | |
| Application Parameter | Storage Temperature (°c) | -40-+60 |
| | Operating Temperature (°c) | -10-+40 |
| | Storage Humidity (RH) | 10%-90% |
| | Operating Humidity (RH) | 10%-90% |
| | IP Rating (Front / Rear) | IP40/IP21 |
| | Module Maintenance | Front or Rear |
| | PSU & Others Maintenance | Front or Rear |
| | Panel Installation Type | Hanging / Stacking / Fixed |
| | Max Rigging QTY | 19 |
| | Certificate | CE,ETL,FCC,ROHS |